SeccoProf EL 38L Electronic Dehumidifier

Italian Design, professional quality stainless steel body, portable light commercial dehumidifier. Helps with control of moisture to prevent mould out breaks and condensation problems.

Key Features at a glance

- Now with electronic digital control. 30-90%RH selectable with continuous or Laundry mode.
- Can run in very low temperatures as low as 2degC! Using the latest electronic logic and hot gas injection.
- Large moisture removal capacity of 38L/day @32degC 80%RH.
- Now with "SuperDry" function which activates for continuous faster dehumidification.
- **Auto Restart Function,** when power returns after a blackout the unit remembers the last setting.
- Features built in Temp/Humidity meter for measuring actual ambient levels.



| Specifications | 38L SeccoProf EL Commercial dehumidifier |
|--------------------------------|--|
| | |
| Model | SeccoProf 38EL |
| Area handling M ³ | 40-330m ³ |
| Water Removal Max (32C/80%RH) | 38 Litres/Day 20L/day@ 27°C/65%rh. |
| AHAM rating @ 27°C/60%rh | 20L/day |
| Adjustable Humidity Range | Digital 30-90%RH in 5%increments |
| Operating Temperature Range | 2 - 35 Celsius Less moisture retrieved at lower temperatures |
| Noise Rating dB | 49 dB @ 1 metre |
| Defrost Type | Auto Defrost cycle for low temp use |
| Refrigerant Type | R134A .33kg |
| Rated Air Flow | High 350m³/hr |
| Housing | Stainless Steel |
| Water tank or Continuous Drain | Large 10 Litre |
| Auto off when tank full | Yes |
| Warranty (Manufacturing) | 2 years RTBwarranty sheet and manual supplied |
| Power | |
| Power Supply | 220V-240V Single Phase Power |
| Power Consumption | 585W 3.6A |
| Running Costs/10hrs Avg. | \$1.72 |
| Auto Restart | Yes |
| Size and Weight | |
| Size L x W x H mm | 435x310x640 |
| Weight | 29kg |
| | |