

LGR Dehumidifier

CT801 PRO

110 Pts | 52L per day @ AHAM

Patent Pending



APPLICATIONS



Flood Damage
Restoration



Basements
& Cellars



Garages



Laundries



Carpet
Drying



Warehouses



Offices



Labs



Superior Stacking

FEATURES

- ✓ Compact Design with XL Performance
- ✓ 230V Model: R32 Refrigerant
115V Model: R410A Refrigerant
- ✓ Built-in Wifi & Bluetooth Technology
- ✓ Free Dry Connect Mobile App
- ✓ Graphical Control Panel
 - GPP Display
 - Humidistat & Timer Control
- ✓ Auto Defrost
- ✓ Automatic Pump Out
- ✓ Superior Stacking
- ✓ Fold-down Handle with Big Wheels
- ✓ Easy Cord and Hose Storage
- ✓ Toolless Filter Access
- ✓ Ducting Option





TECHNICAL DATA

Capacity @ AHAM	52L 110 pts. / Day	Defrost Type	Hot Gas Bypass
Capacity @ SATURATION	90L 190 pts. / Day	Drain Hose	32 ft 10 m
Amperage	10.0 Amps (115V) 5.0 Amps (230V)	Refrigerant	R410A (115V) R32 (230V)
Air Flow	700 m ³ /h	Power Cord	25 ft 7.6 m
Power Consumption	1150 Watt	Air Filter	MERV-10 Filter
Operating Range	33°F-100°F 1°C - 38°C	Condensate Pump	Yes
Operating Humidity Range	20% RH Upto 90% RH	Weight	86 lbs 39 KG
Housing	Rotomolded	Dimensions (WxDxH)	16.5 x 25.4 x 18.2 in. 420 x 645 x 463 mm
Noise Level	65 dB(A)	Safety	CE & CSA

Specifications are subject to change without notice. Some values are approximate.

